

PERSONAL BERYLLIUM AIR SAMPLER

Model ~ MINI-AIR-Be

FEATURES:

- REAL-TIME AIR FLOW METER
- SAMPLE COLLECTION OF BERYLLIUM PARTICULATES
- FLOW RATE 3 LPM.
- RECHARGEABLE BATTERIES WITH 230 VAC CHARGER
- INTEGRATED EXPOSURE
- CAN DRAW AIR FROM ROOM OR BREATHING ZONE
- QUICK CHANGE Be FILTER DISK
- DATA ARCHIVE & RETRIEVAL
- USB DATA PORT
- **OPTIONAL:** BELT CLIP
- **IP65**

DATA ACCESS

DATA
STORAGE >

Air Pump >
Flow Meter >
Filter Disk
Holder >
Filter Disk >

SAMPLE
COLLECTION
INLET >



APPLICATION:

The **MINI-AIR Be** air monitor assures safety against airborne Beryllium contamination by means of constant Beryllium collection. It provides integrated exposure Be sample.

The **MINI-AIR-Be** is sensitive and versatile. Although designed as an industrial workplace and nuclear breathing air measurement system, it may also be used to monitor fume hoods and stack effluent.

DESCRIPTION:

The **MINI-AIR-Be** uses Beryllium trapping glass fiber filter disks (47mm and 140 mm diameter) in TA's unique quick change, no leak filter holder.

- ✓ Air is drawn by a 3 lpm Be pump through the filter and exhausted to the room or through an optional hose. An Inlet hose may be attached to allow monitoring of hoods, glove boxes, stacks, etc.
- ✓ Power is controlled by an On / OFF rocker switch.
- ✓ The unit is completely self-contained and portable.
- ✓ No-Leak Filter holders for 47 mm and 14 mm filters.
- ✓ Complete with Be-fil-47 and Be-fil-140 (40) filter disks of each size
- ✓ Data Storage includes: Last low flow rate, elapsed clock time, accumulated volume is save into memory until cleared for next sampling.



TECHNICAL ASSOCIATES

7051 ETON AVENUE, CANOGA PARK, CALIFORNIA 91303

PHONE: 818-883-7043 | FAX: 818-883-6103

SALES@TECH-ASSOCIATES.COM | TECH-ASSOCIATES.COM | USNUCLEARCORP.COM

DIVISION OF



USNUCLEARCORP

OTC08-UCLE

PERSONAL BERYLLIUM AIR SAMPLER

Model ~ MINI-AIR-Be

SPECIFICATIONS:

Air Flow Pump:	Miniature 3 Liter/min Pump and Filter holder.
Flow Range:	0.8-5 LPM (800-5000 cc/min) with Universal Low Flow Holder
Flow Accuracy:	±5% of compensation range
Compensation Range:	800-5000 cc/min
Power:	Rechargeable Batteries with Charger.
Air Flow Meter:	Displays flow rate 3.0 LPM.
Data:	Data Archive & Retrieval USB Data Port
Filters:	47mm and 140 mm diameter filter disks (Befil-47 and Be-fil-140 Includes 40 filter disks of each size
Inlet Sniffer Hose:	3 Feet (Standard) (1 meter)
OPTIONAL Exhaust Hose:	3 Feet (Standard) (1 meter)
Case:	Air Pump & Filter, & Filter Disk Holder housed in polished blue aluminum.
Weight & Dimensions:	
Air Sampler Dimensions:	2.25" Dia x 12.5" L x 4.5"W x 4"H x 2"D. (11.4 cm x 10.2 cm x 5 cm) (Nominal)
Weight:	1 lb.(0.4 kg)

Easy Filter Change Procedure:

Flow rate has been preset (user can change those if desired).

1. Download data prior to replacing disk.
2. Remove filter disk with tweezers and place in sealed sample envelop
3. Give filter disks to chemical lab for analysis
4. Filter must be clean at start of each new air sample.
5. Put in clean filter disk.
6. Clip it to your belt. (If using clip.)
7. Turn on Pump.

OPTIONS:

- Other filter sizes per spec
- Shrouded probe inlet
- Exhaust hose 3' standard



TECHNICAL ASSOCIATES

7051 ETON AVENUE, CANOGA PARK, CALIFORNIA 91303

PHONE: 818-883-7043 | FAX: 818-883-6103

SALES@TECH-ASSOCIATES.COM | TECH-ASSOCIATES.COM | USNUCLEARCORP.COM

DIVISION OF



USNUCLEARCORP

OTCQB:UCLE